CLASSIC BRASS

JAMESTOWN, NEW YORK

M/P SETS - EURO SECTIONAL

FIFTH AVENUE COLLECTION





M/P - EURO SECTIONAL

APPLICATIONS

7460 Lever Euro M/P Sectional Set - ENTRANCE

7461 Lever Euro M/P Sectional Set - FULL DUMMY

7462 Lever Euro M/P Sectional Set - ACTIVE DUMMY

7463 Lever Euro M/P Sectional Set - PATIO

Above sets include 7573 Lever

MATERIALS


Solid Brass

HOW TO ORDER

- 1. Specify application.
- 2. Specify finish. If split finish is required, please indicate exterior/interior.
- 3. Specify door thickness. Standard thickness is 1-3/4".
- 4. Specify hand of door RH/LH.
- $\label{eq:continuous} 5. \ \ Specify fixed or active exterior lever when ordering active \\ dummy set.$

REMEMBER

- 1. VERIFY door prep will be fully covered by sectional trim.
- 2. Standard euro profile application is LEVER HIGH 92mm (hub-cylinder spacing).
- 3. Door thickness greater than 1-3/4" will require longer euro cylinders and/or offset cylinders. $62\,\text{mm}$ K x T/P ($31\,\text{mm}$ x $31\,\text{mm}$) and $31\,\text{mm}$ Half Cylinder is standard for 1-3/4" doors.
- $4.\,$ Cylinders INCLUDED with all applications (collection turnpiece attached).
- 5. Custom rose and cylinder collar sizes available.
- 6. ONE STEP edge profile is standard. Specify TWO STEP, BEVEL or SLAB edge profile if required.
- 7. Strike not included.
- 8. Euro offset cylinders and custom lengths available upon request.





SET COMPONENTS

Lever Euro M/P Sectional Set - ENTRANCE includes two rosettes, two levers, 4" straight spindle (8mm), euro profile cylinder - 62mm - $K \times TP$ and surface mounting screws.

Lever Euro M/P Sectional Set - FULL DUMMY includes two rosettes, two levers, 4" straight spindle (8mm), full dummy mounting hardware and surface mounting screws.

Lever Euro M/P Sectional Set - ACTIVE DUMMY includes two rosettes, two levers, 4" swivel spindle (8mm), full dummy mounting hardware for exterior rosette.

Lever Euro M/P Sectional Set - **PATIO** includes two rosettes, two levers, one euro cylinder collar, euro profile half cylinder (31mm), 4" straight spindle (8mm) and surface mounting screws.


SQUARE ESCUTCHEON


EDGE OPTIONS

ONE STEP EDGE


Standard


TWO STEP EDGE






BEVEL EDGE





SLAB EDGE





HOW TO ORDER

- Specify EDGE DETAIL — ONE STEP edge option is standard. If alternate EDGE DETAIL is required make sure to specify as SUB (example - SUB BEVEL).

REMEMBER

- Custom escutcheon sizes are available.
- Standard escutcheon thickness is 1/4" alternate thickness available upon request.
- · Contact us to discuss custom edge details or profiles.

CLASSIC BRASS

JAMESTOWN, NEW YORK

SIGNATURE FINISHES

SOLID BRASS FINISHES

















POLISHED ANTIQUE NO LACQUER (PANL)

Polished Brass — No Lacquer (PBNL) Revere Brass (RB) Revere Tarnished (RT)

Polished Brass (PB)

Burnished Brass (BB) Oil Rubbed Bronze (BZ) Kensington (KN)

Polished Antique (PA)

LEVEL 1 Antique Brass (AB)



Antique Burnished Nickel (ABN)

Antique Burnished Brass (ABB)

Polished Antique — No Lacquer (PANL)





KENSINGTON



MATTE BLACK (MB)



POLISHED ANTIQUE



















Satin Nickel (SN) Weathered Antique Nickel (WA) Weathered Copper (WC) Weathered Nickel (WN)



WEATHERED BRONZE



WEATHERED COPPER



WEATHERED NICKEL







LEVEL 3

Antique Polished Silver (APS) Polished Silver (PS) Satin Silver (SS)

PRICE ON REQUEST

Polished Gold (PG) Satin Gold (SG)

Custom finishes available on request.