CLASSIC BRASS

JAMESTOWN, NEW YORK

ENTRANCE LEVER SETS

FIFTH AVENUE COLLECTION





ENTRANCE LEVER SETS

APPLICATIONS

7616 Lever Mortise Entrance Set **7617** Lever Mortise Entrance Set - FULL DUMMY

7618 Lever Latch x Auxiliary Deadbolt Set7619 Lever Latch x Auxiliary Deadbolt Set - FULL DUMMYAbove sets include 7773 Lever

MATERIALS

Solid Brass

SPINDLES


8mm SQ (standard)

HOW TO ORDER

- 1. Specify application.
- 2. Specify finish. If split finish is required, please indicate exterior/interior.
- 3. Specify door thickness. Standard thickness is 1-3/4".
- 4. Specify hand of door RH/LH.
- 5. Specify backset.
 - standard for mortise lock is 2-1/2".
 - standard for latch x auxiliary deadbolt is 2-3/8".

REMEMBER

- 1. Standard mortise lock is 2-1/2" EE. Specify 2-3/4" if required.
- 2. Standard latch x auxiliary deadbolt: 5-1/2" c-c and 2-3/8" backset. If required, specify 2-3/4" backset.
- 3. All levers are interchangeable.
- 4. A door thickness greater than 1-3/4" will require a #9901 thick door kit for mortise application.
- 5. Custom escutcheon sizes and drilling available.
- 6. ONE STEP edge profile is standard. Specify TWO STEP, BEVEL, or SLAB edge profile if required.
- 7. Oval slot head wood screws (4/ea) are standard on the escutcheons.





SET COMPONENTS

Entrance Lever Set - Mortise Lock includes exterior plate, interior plate with turnpiece, two levers, 4" swivel spindle (8mm), Accurate 9124 L x L mortise lock (2-1/2" backset), faceplate, strike 1-1/4" LTC, dust box, mortise cylinder and mounting hardware.

Entrance Lever Set - Latch x Auxiliary Deadbolt includes exterior plate, interior plate with turnpiece, two levers, passage latch L x L (2-3/8" backset), 4" straight spindle (8mm), auxiliary deadbolt (2-3/8" backset), rim cylinder, turnpiece, latch faceplate, deadbolt faceplate, full lip strike, deadbolt strike, dust boxes and mounting hardware. NOTE: our standard spacing between lever hub and auxiliary deadbolt is 5-1/2" c-c.

 $\label{lem:continuous} \textbf{Entrance Lever Set} - \textbf{FULL DUMMY} \ includes \ exterior \ plate, interior \ plate, \\ two \ levers, 4" \ straight \ spindle \ (8mm) \ and \ full \ dummy \ mounting \ hardware.$


SQUARE ESCUTCHEON


EDGE OPTIONS

ONE STEP EDGE

Standard


TWO STEP EDGE






BEVEL EDGE

SLAB EDGE







HOW TO ORDER

- Specify EDGE DETAIL — ONE STEP edge option is standard. If alternate EDGE DETAIL is required make sure to specify as SUB (example - SUB BEVEL).

REMEMBER

- · Custom escutcheon sizes are available.
- Standard escutcheon thickness is 1/4"— alternate thickness available upon request.
- · Contact us to discuss custom edge details or profiles.

CLASSIC BRASS

JAMESTOWN, NEW YORK

SIGNATURE FINISHES

SOLID BRASS FINISHES

















POLISHED ANTIQUE NO LACQUER (PANL)

Polished Brass — No Lacquer (PBNL) Revere Brass (RB) Revere Tarnished (RT)

Polished Brass (PB)

Burnished Brass (BB) Oil Rubbed Bronze (BZ) Kensington (KN)

Polished Antique (PA)

LEVEL 1 Antique Brass (AB)



Antique Burnished Nickel (ABN)

Antique Burnished Brass (ABB)

Polished Antique — No Lacquer (PANL)





KENSINGTON



MATTE BLACK (MB)



POLISHED ANTIQUE



















Satin Nickel (SN) Weathered Antique Nickel (WA) Weathered Copper (WC) Weathered Nickel (WN)



WEATHERED BRONZE



WEATHERED COPPER



WEATHERED NICKEL







LEVEL 3

Antique Polished Silver (APS) Polished Silver (PS) Satin Silver (SS)

PRICE ON REQUEST

Polished Gold (PG) Satin Gold (SG)

Custom finishes available on request.