CLASSIC BRASS

JAMESTOWN, NEW YORK

M/P SETS - EURO

SAVANNAH COLLECTION



M/P SETS - EURO

1-3/4" X 12" MULTI POINT SETS

8250 Lever Euro M/P Set - ENTRANCE

8251 Lever Euro M/P Set - FULL DUMMY

8252 Lever Euro M/P Set - ACTIVE DUMMY

8253 Lever Euro M/P Set - PATIO

Above sets include 8357 Lever

2-3/8" X 12" MULTI POINT SETS

8256 Lever Euro M/P Set - ENTRANCE

8257 Lever Euro M/P Set - FULL DUMMY

8258 Lever Euro M/P Set - ACTIVE DUMMY

8259 Lever Euro M/P Set - PATIO

Above sets include 8357 Lever

MATERIALS

Solid Brass

SPINDLES


8mm SQ (standard)

HOW TO ORDER

- 1. Specify application.
- 2. See our M/P Check Sheet (Form 500) for additional information.
- 3. Specify finish. If split finish is required, please indicate exterior/interior.
- 4. Specify door thickness. Standard thickness is 1-3/4".
- 5. Specify hand of door RH/LH.
- Specify fixed or active exterior lever when ordering active dummy set.

REMEMBER

- 1. Complete our M/P Check Sheet (Form 500).
- 2. Standard euro profile application is LEVER HIGH $92\mathrm{mm}$ (hub-cylinder spacing).
- 3. All levers are interchangeable.
- 4. Door thickness greater than 1-3/4" will require longer euro cylinders and/or offset cylinders. $62\,\text{mm}$ x K x TP ($31\,\text{mm}$ x $31\,\text{mm}$) and $31\,\text{mm}$ Half Cylinder is standard for 1-3/4" doors.
- 5. Cylinders INCLUDED with all applications (collection turnpiece attached).
- 6. Strike not included.
- 7. Custom drilling available.
- $8.\,$ Euro offset cylinders and custom lengths available upon request.





SET COMPONENTS

Lever Euro M/P Set - **ENTRANCE** includes two escutcheons, two levers, 4" straight spindle (8mm), euro profile cylinder - 62mm - K x TP and mounting hardware. NOTE: our standard spacing between lever hub and the profile cylinder is 92mm.

Lever Euro M/P Set - FULL DUMMY includes two escutcheons, two levers, 4" straight spindle (8mm), two dummy mount plates and mounting hardware.

Lever Euro M/P Set - **PATIO** includes exterior escutcheon, interior escutcheon, two levers, 4" straight spindle (8mm), euro profile half cylinder - 31mm and mounting hardware. NOTE: our standard spacing between lever hub and the profile cylinder is 92mm.

CLASSIC BRASS

JAMESTOWN, NEW YORK

SIGNATURE FINISHES

SOLID BRASS FINISHES





















POLISHED ANTIQUE NO LACQUER (PANL)

Polished Brass (PB) Polished Brass — No Lacquer (PBNL) Revere Brass (RB) Revere Tarnished (RT)

Antique Burnished Brass (ABB)

Polished Antique — No Lacquer (PANL)

Burnished Brass (BB) Oil Rubbed Bronze (BZ) Kensington (KN)

Polished Antique (PA)

Satin Brass (SB)

LEVEL 1 Antique Brass (AB)

Satin Brass — No Lacquer (SBNL) Tarnished (TN)

Weathered Brass (WB)

Weathered Bronze (WZ)

LEVEL 2







KENSINGTON


















WEATHERED BRONZE



WEATHERED COPPER



WEATHERED NICKEL







Burnished Nickel (BN) Matte Black (MB) Polished Chrome (PC) Polished Nickel (PN) Revere Nickel (RN) Satin Nickel (SN) Weathered Antique Nickel (WA) Weathered Copper (WC)

Weathered Nickel (WN) LEVEL 3

Antique Polished Silver (APS) Polished Silver (PS) Satin Silver (SS)

PRICE ON REQUEST

Polished Gold (PG) Satin Gold (SG)

Custom finishes available on request.